

Model No.: HD-CB802 Self-Propelled Belt Loader

Model No.: HD-CB802 Self-Propelled Belt Loader

The HD-CB802 is a reliable and widely used belt loader for cargo or baggage transport in the ramp handling. It is in compliance with IATA AHM 905, IATA AHM 910, IATA AHM 913 and GB1589, GB4785-2007, GB7258-2004, MHT-6048-2008 requirements.



FEATURES:

- *Engine: Cummins, QSF2.8T3NA49, 36kw/2500 rpm, 186Nm/1100-1500rpm
- *Emission: EUStage IIIA, EPA 40 CFR Part 89.112 Tier 3
- *With movable engine cover.
- *Transmission: OKAMARU Y43280D, Automatic, 1 forward/1 backward
- *Hydraulic pump: PERMCO, 1171011202
- *Hydraulic motor: EATON, JS-250(030-0426)
- *Manual pump for emergency operation.
- *Hydraulic steering system.
- *Hydraulic stabilizers ensures safety and stabilization.
- *Brake Front/Rear: hydraulic disc brake/Hydraulic drum brake.
- *Electrical system: DC 12V

SPECIFICATIONS:

- *Overall dimensions (LxWxH): 8040x2080x1890 (with cab)
- *Maximum speed: 30km/h
- *Turning radius: 8500mm
- *Wheelbase: 3000mm
- *Track F/R: 1725mm/1680mm
- *Maximum driving ramp: 30°
- *Ground clearance: 130mm
- *Self weight: Approx. 3300kgs
- *Belt width: 700mm
- *Belt working speed: 0.3 - 0.5m/s
- *Belt load capacity: 135kgs/m
- *Front end working heights: 1100 - 4200mm
- *Rear end working heights: 400 - 1500mm
- *Maximum beam angle: 29°
- *Working temperature: -40°C ~ +65°C
- *Tyre front/rear: 7.00R15-10PR

OPTIONAL FEATURES

- *Full driving cab
- *Canopy
- *Air conditioning.



yumbo



Since 1959

www.handlingyumbo.com
info@handlingyumbo.com

Model No.: HD-CB803

Towable Belt Loader

Model No.: HD-CB803

Towable Belt Loader

The HD-CB803 is a reliable and widely used belt loader for cargo or baggage transport in the ramp handling. It is in compliance with IATA AHM 905 ,IATA AHM 910,IATA AHM 913 and GB1589, GB4785-2007,GB7258-2004 , MHT-6048-2008 requirements.



FEATURES:

- *Engine: KUBOTA Z482-E3B-SAE-2, 0.5L,9.9kw/3600rpm, 29.7Nm/2600rpm
- *Emission: EU Stage IIIB/US EPA Tier4
- *Hydraulic pump: CHANGYUAN, CBT-FA412.5-AFR
- *Hydraulic motor: EATON, 036-0027-002
- *Slowly moving motor operated by hand.
- *Parking brake.
- *Electrical system: DC 12V

SPECIFICATIONS:

- *Overall dimensions (LxWxH): 9190x1580x1720
- *Maximum towing speed: 25km/h
- *Wheelbase: 4080mm
- *Track F/R: 1335mm/600mm
- *Ground clearance: 110mm
- *Self weight: 1960kgs
- *Belt width: 700mm
- *Belt working speed: 0.16 - 0.5m/s
- *Belt load capacity: 135kgs/m
- *Front end working heights: 1200 - 4200mm
- *Rear end working heights: 475 - 1700mm
- *Working temperature: -40℃ ~+65℃
- *Tyre front/rear: 7.00-9 solid rubber / 4.00-8 solid rubber

OPTIONAL FEATURES

- *Canopy



yumbo



Since 1959

www.handlingyumbo.com
info@handlingyumbo.com