

Ambulift Truck

Model No.: HD-ABL5800



Ambulift Truck

Model No.: HD-ABL5800

The HD-ML5800 is a reliable design of ambulift truck with the service height of 2400mm-5700mm, which can provide safe and comfortable services for PRM passengers to/from aircraft. It is suitable for aircrafts of B737, B747, B757, B767, B777, MD90, MD11, DC10, A300, A310, A318, A319, A320, A321, A330, A340, A380, CONCORDE, TU154M, TL-96-300. It is in compliance with IATA AHM 904, IATA AHM910, AHM913, AHM914 and IATA AHM921.

SPECIFICATIONS:

*Service height:	2400mm ~ 5700mm
*Dimensions:	6920x2400x3800mm
*Carriage dim.	4380x2280x2258mm
*Wheelbase:	3815mm
*Maximum speed:	50km/h
*Gross weight:	Approx.7300kgs
*Carriage load:	1000kgs
*Front Fixed platform dim.:	2200x850mm
*Front platform capacity:	500kgs
*Front platform adjustable range:	0-600mm
*Rear Platform dim.:	1480x2190mm
*Rear platform capacity:	400kgs
*Rear platform adjustable range:	0-1440mm

FEATURES:

- *Chassis: ISUZU 600P
- *Engine: ISUZU 4KH1-TCG40 Diesel
- *Emission: GB IV
- *Transmission: Manual
- *Dual hydraulic circuit drum brake with ABS
- *Leaf spring Suspension
- *Hydraulic steering System
- *4 Hydraulic stabilizers with safty working system.
- *Hydraulic pump: Permco
- *Manual pump and emergency electrical pump (Bucher) for emergency operation.
- *Warm and Cool air condition .



www.handlingyumbo.com
info@handlingyumbo.com

Ambulift Truck

Model No.: HD-ABL5800D

Ambulift Truck

Model No.: HD-ABL5800D

The HD-5800D is a reliable design of ambulift truck with the service height of 2500mm~5800mm, which can provide services to aircrafts of B737, B747, B757, B767, B777, MD90, MD11, DC10, A300, A310, A318, A319, A320, A321, A330, A340, A380 (first level door), CONCORDE, TU154M, TL-96-300. It is in compliance with IATA AHM 905, IATA AHM910, AHM913, AHM915, IATA AHM916 and MH/T6016 -2017.



SPECIFICATIONS:

*Service height:	2500mm - 5800mm
*Dimensions:	8990×2460×3800mm
*Carriage dim.	6520×2300×2350mm
*Wheelbase:	5550mm
*Maximum speed:	50km/h
*Gross weight:	Approx. 10150kgs
*Outer turning diameter:	20000mm
*Carriage load:	2500kgs
*Fixed platform load:	1000kgs
*Movable platform load:	500kgs
*Front platform adjustable range:	0-600mm (Front/back)
*Front platform adjustable range:	0-500mm (Left /Right)
*Rear platform capacity:	400kgs
*Rear platform adjustable height:	0 - 1530mm

FEATURES:

- *Chassis: ISUZU QL1100A8PAY
- *Engine: ISUZU 4HK-TC51 Diesel
- *Emission: GB V (EU IV)
- *Transmission: Manual (Allison 1000 Automatic for option)
- *Dual hydraulic circuit drum brake with ABS
- *Leaf spring Suspension
- *Hydraulic steering System
- *4 Hydraulic stabilizers with safty working system.
- *Hydraulic pump: Permco
- *Manual pump and emergency electrical pump (Bucher) for emergency operation.
- *Warm and Cool air condition



Since 1959

www.handlingyumbo.com
info@handlingyumbo.com